

# SEAL COOL 2190

## PREMIUM SEMI-SYNTHETIC METALWORKING FLUID

### General Description

Seal Cool 2190 is a high performance semi-synthetic coolant for machining and grinding of ferrous and non-ferrous alloys. Seal Cool 2190 is formulated with a unique blend of raw materials that give this product exceptional biostability.

- Versatile – Used in variety of applications.
- Excellent Corrosion Protection
- Safe and Mild.
- Long Sump Life- Biostatic
- Good lubricity.
- Cleanliness
- Nitrite free.

### Typical Properties

Concentrate Appearance	Amber
Density (pounds/gallon)	8.5
Flash Point (C.O.C.)	None
pH @ 10%	9.2
Odor	Bland
Residue	Liquid Film
Metal Compatibility	All metals

### Storage and Handling

Seal Cool 2190 can be stored either indoors or outdoors. If outdoor storage is used, the product should be brought to room temperature prior to use. Product is not for internal consumption. Seal Cool 2190 is non-irritating and non-toxic when used properly.

### Application

Honing, Tapping, Reaming	5-10%
Milling, Drilling, Turning	5-10%

No warranty, guarantee or representation is made herein with respect to the use of the products referenced herein or otherwise except that said products conform to the chemical description shown on their labels.

EXCEPT AS SET FORTH ABOVE, GALAXY ASSOCIATES, INC. DISCLAIMS ALL WARRANTIES, WHETHER EXPRESSED OR IMPLIED, WITH RESPECT TO THE PRODUCTS, WHETHER AS TO QUALITY, CONDITION, PERFORMANCE, MERCHANTABILITY, FITNESS FOR ANY PURPOSE OR OTHERWISE AND IN NO EVENT SHALL GALAXY ASSOCIATES BE LIABLE FOR ANY CONSEQUENTIAL DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE PRODUCTS OR THEIR USE.

## SEAL COOL 2190

### Testing

#### REFRACTOMETER READING

2%	1.2
4%	2.4
6%	3.6
8%	4.8
10%	6.0

### Regulatory Information

CAUTION: Eye and skin contact may cause irritation with prolonged contact. Harmful if swallowed. Do not get in eyes or on skin. Do not take internally.

Open drums slowly to vent. Handle with rubber gloves, rubber apron, chemical goggles, face mask, and rubber boots. Avoid breathing vapor or mist. When preparing solutions or making additions, add only to cool water with stirring. Improper addition of this product can cause splash-back, resulting in serious chemical burns. Eyewash and safety shower must be immediately available. Personnel handling this product should be acquainted with its characteristics and dangers. Do not mix with acids. Keep out of the reach of children.  
L02-01

Consult MSDS for complete safety information.

### Attention

When empty, the container may still be hazardous. Because containers, even after they have been emptied, still retain product residues (vapor, liquid or solid), all labeled hazard precautions must be observed. If emptied product containers of 119 gallons or greater volume are to be shipped, DOT requires the containers be triple rinsed (or equivalent) to remove any residue and DOT placards be removed or covered with plain placards before they can be shipped as empty containers.

Issued 3/13/2007, Supercedes New

No warranty, guarantee or representation is made herein with respect to the use of the products referenced herein or otherwise except that said products conform to the chemical description shown on their labels.

EXCEPT AS SET FORTH ABOVE, GALAXY ASSOCIATES, INC. DISCLAIMS ALL WARRANTIES, WHETHER EXPRESSED OR IMPLIED, WITH RESPECT TO THE PRODUCTS, WHETHER AS TO QUALITY, CONDITION, PERFORMANCE, MERCHANTABILITY, FITNESS FOR ANY PURPOSE OR OTHERWISE AND IN NO EVENT SHALL GALAXY ASSOCIATES BE LIABLE FOR ANY CONSEQUENTIAL DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE PRODUCTS OR THEIR USE.